



ENHANCED

AUDIO QUALITY





DAMPENING



NOISE REDUCTION



HEAT RESISTANT



ENHANCED CABIN COMFORT

=≡ NOISE • HEAT • VIBRATION ≡=



BY SUPERLON®

Your Solution To Sound Insulation

Acoustec PRO

Acoustec **PRO** is an open cell foam composite designed specifically for sound absorption and vibration dampening. The high density and rigidity nature also deliver sound proofing features making Acoustec **PRO** the best all in one sound insulation product in the market.

Acoustec LITE


Acoustec LITE is an open cell nitrile foam. It is more cost-effective option for noise reduction and vibration dampening. Similar features and performance to Acoustec **PRO**, with less sound proofing features.

Application

It can be used in a wide array of applications such as automotive, music studios and building and construction.

Acoustec **PRO** and LITE inherent flexibility and open cell structure simplifies complex requirements and installation.

Acoustec PRO Comparison With LITE



	1/3 Octave	Sound Absorption Coefficient α		
Acoustec Performance based on 3/8" (10mm) Thickness		PRO	LITE	ASTM C423
	250 Hz	0.07	0.06	
	630 Hz	0.38	0.25	
	800 Hz	0.60	0.43	
	1250 Hz	0.84	0.70	
	2500 Hz	0.82	0.30	
	5000 Hz	0.74	0.40	
	NRC	0.50	0.30	

Thickness		Size	Pcs
Inches	mm	Metres	Per Carton
3/8"	10	0.50 X 0.95	15
1/2"	13	0.50 X 0.95	12
5/8"	16	0.50 X 0.95	10
3/4"	19	0.50 X 0.95	8
1"	25	0.50 X 0.95	6

Features & Performance

Noise Reduction
 Impressive Noise Reduction Coefficient (NRC)

Enhance Audio Quality
 Less noise translates to better and improved audio quality from the car's stereo system

Vibration Dampening
 Rattles and vibrations will disappear

Heat Resistant

The nitrile foam composite can also reduce heat transmission through the vehicle's steel panels

Enhance Cabin Comfort

Less noise also translates to better cabin ambience. Conversations with fellow passengers made clearer without the need to raise voices.

Installation & Results

- Easy installation.
- Clean the surface area thoroughly then just cut, peel and paste.
- For the ultimate result and desired performance please contact us for the best solution.





SUPERLON WORLDWIDE SDN BHD

Lot 2567 Jalan Sungai Jati, 41200 Klang, Selangor D.E, Malaysia Web: www.superlon.com.my | Email: inquiry@superlon.com.my Tel: +603-3372 3888 Fax: +603-3371 5888